# Alpa Coachbuilt

The motorhome for travelling couples. With generous space, a huge panoramic seating group and comfortable single beds in the alcove, this motorhome is ideally suited for comfortable travelling as a couple. And even in freezing temperatures, because the heated double floor with frost-protected water installation makes it absolutely winterproof.



#### Technical info

Overall length, approx.	733 - 858 cm
Overall width, approx.	233 cm
Overall height, approx.	327 cm
Headroom in living area, approx.	209 cm

Maximum values partly not possible for all models or only in connection with certain options.

### Plus factors

- 180 hp (136 kW) Multijet engine, 9-speed torque converter automatic transmission, automatic climate control, LED daytime running lights, multifunction leather steering wheel and state-of-the-art driving assistance systems
- + Ideal driving characteristics: Premium low-frame chassis with 145 mm lowering and up to 4.8 t or 5.4 t permissible total mass
- + Absolute winter resistance due to heated raised floor with installation laid frost-protected
- + Lifetime Plus superstructure technology with absolutely rot-proof and durable wall construction
- + Huge panoramic round seating area with plenty of space to eat and linger
- + Comfortable lengthwise single beds with 195 x 80 cm and 205 x 80 cm lying area in the alcove incl. large access steps




### Upholstery



+ Upholstery Samir



+ Real leather upholstery Colin O



+ Upholstery Melia

### Wood décor



+ Wood décor Ashton

O optionally available



### Alpa Coachbuilt Technical info

Alpa Coachbuilt		A 6820-2	A 7820-2
Standard chassis		Fiat Ducato Maxi AL-KO Low Platform	Fiat Ducato Maxi AL-KO Low Platform 3-axle
Emission standards		Euro VI-E	Euro VI-E
Overall length, approx.	cm	733	858
Overall width, approx.	cm	233	233
Overall height, approx.	cm	327 1)	327 1)
Headroom in living area, approx.	cm	209	209
Towable load braked/unbraked	kg	1750 / 750	1800 / 750
Wheelbase, approx.	mm	4070	4600
Bed dimension alcove, L x W, approx. cm	cm	205 x 80 / 195 x 80 / 210 x 155	205 x 80 / 195 x 80 / 210 x 155
Bed dimension: Rear bed, L x W, approx.	cm	210 x 170	210 x 210 - 150
Sleeping berths standard / max.		4	4
Standard engine		180 MultiJet 3 Power	180 MultiJet 3 Power
kW (bhp)		132 (180)	132 (180)
Mass in running order (+/-5%)*	kg	3571 (3392 to 3750)*	4060 (3857 to 4263)*
Manufacturer-specified mass for optional equipment*	kg	871	564
Technically permissible maximum laden mass*	kg	4800	5000
Permitted number of seats (including driver)*		4	4
Refrigerator volume (thereof freezer), approx.	1	153 (29)	177 (35)
Waste water tank, approx.		137	137
Fresh water tank capacity, total/ Fresh water tank capacity at driving filling	I	140 / 20	140 / 20
Measurement storage opening left (W x H)	cm	95 x 105	105 x 105
Measurement storage opening right (W x H)	cm	95 x 105	105 x 105

O Optional equipment — Not possible ● Standard equipment ◆ Mandatory △ Not known at the time of publication

### \* INFO

The specified mass in running order is a default value defined in the typeapproval procedure. Due to manufacturing tolerances, the actual weighed mass in running order may deviate from the value stated above. Deviations of up to  $\pm$  5 % of the mass in running order are legally permissible and possible. The permissible range in kilograms is given in brackets after the mass in running order. The manufacturer-specified mass for optional equipment is a calculated value for each type and layout that Dethleffs uses to determine the maximum weight available for factory-fitted optional equipment. The limitation of optional equipment is intended to ensure that the minimum pay-mass, i.e. the legally prescribed free mass for baggage and retrofitted accessories, is actually available for the vehicle load capacity of the vehicles delivered by Dethleffs. The real weight of your vehicle ex works can only be determined when it is

weighed at the end of the line. If, in exceptional cases, the weighing shows that the actual load capacity falls below theminimum pay-mass despite limiting the optional equipment due to a permissible weight deviation, we will check together with your trade partner and you whether we should, for example, increase the load capacity of the vehicle, reduce the number of seats or remove optional equipment before delivering the vehicle. The technically permissible maximum laden mass of the vehicle and the technically permissible maximum mass on the axle must not be exceeded. Detailed information & explanations on the subject of weight and the configuration of the vehicle can be found in the section Legal information. For a more detailed description of all mandatory technical dependencies, please refer to the explanations on the footnotes.

## Standard equipment

A 0020-2	C-0C87 0
Z	
_	_

	Fiat chassis			
	Fiat Ducato Maxi ALKO low platform (4,800 kg incl. air suspension rear axle, reinf. springs, alloy rims) MultiJet 180 (2.2 l / 132 kW / 180 hp) HD, 9-speed torque converter autom. trans.	•	_	-
	Fiat Ducato Maxi ALKO low-platform 3-axle (5,000 kg) MultiJet 180 (2.2 l / 132 kW / 180 hp) Heavy Duty, 9-speed torque converter automatic transmission	-		
	Right-hand drive chassis			
	Steel rims 16" (225/75 R16C) incl. full wheel covers	-		
	Weight upgrade			
	Single folding seats rear right and left incl. Isofix, bed construction seating group as well as the weight upgrade 4,800 kg with air spring HA, reinforced coil springs VA and 16" aluminium rims.	•	-	-
	Fiat chassis features			
ĺ	ABS (anti-lock braking system) / EBD (electronic brakeforce distribution)		•	,
	Anti-theft device		•	
	Automatic Brake Assist after a collision			
	Bench with 3-point seatbelts for seats facing away from driving direction incl. bed convert for seating lounge (1944)	-	•	
	Bumper painted in white			
	Cab blackout blinds		•	
	Captain seats for driver and front passenger, swivel function			
	Chassis in right-hand drive version		•	
	Crosswind Assist		•	
	Cruise control		•	
	Cup holder in the centre of the dashboard		•	
	DAB+ radio antenna integrated into right exterior mirror		•	
	Dashboard with aluminium application		•	
	Diesel tank 90 litre incl. 19L AdBlue tank		•	
	Driver and passenger airbags			
	Driver and passenger detection		•	
	Driver's cab automatic A/C			
	ESP incl. ASR, Traction Plus, Hill Holder and Hill Descent Control		•	
	Electrically adjustable and heated exterior mirrors incl. blind spot mirror and integrated turn indicator			
	Emergency Brake Assist with pedestrian and cyclist detection		•	
	Exterior colour chassis white			
	Front grille, high-gloss black with chrome trim		•	
	Front-wheel drive			
	Headlights with black rim		•	
	Height and tilt adjustment and double armrests for driver and passenger seat			
	High Beam Assist			
	Keyless Entry & Go			
	LED daytime running lights		•	
	Lane Keep Assist			
	Leather steering wheel and gear knob withleather sleeve			
	Light Assist			
	Padded double armrests, fabric cover			
	Rain sensor			
	Rear corner steadies (2 pieces)			
	Skid plate high-gloss black			
	Steering wheel with control elements			
	Traffic Sign Assist			
	Trailer Stability Assist	•		
	Tyre inflation kit and towing eye			
	Exterior features			
ĺ	70 cm wide living room door with window and blackout, electric closing aid and gas pressure damper as hold-open device			
	Central locking additionally for garage doors	•		
	Central locking for the driver's cab and habitation door			

### Standard equipment

Standard equipment	A 6820-2	A 7820-2
Dethleffs Exclusive rear light carrier with ShapeLine LED taillights and 3rd brake light integrated in rear spoiler	•	
Double floor storage, some of which can be loaded across almost the entire vehicle width		
Floor thickness: 43 mm, side wall thickness: 34mm and roof thickness: 35 mm		
Flyscreen habitation door		
GRP roof		
Habitation access with comfortable coupe entrance		
Habitation access with comfortable, wide, electric step	٠	•
Lifetime Plus construction technology: rot-free superstructure with no wood inserts, XPS insulation with GRP cladding on the underslung and roof		
Opening window in overcab right	•	•
Panoramic skylight 75x105 cm above U-shaped seating	-	
Rear garage: two garage door with one-hand operation, rear lowering (250 kg), heated, lashing rails, LED lights across the entire width, 230 V socket, GRP anti-slip flooring and fleece cove	•	•
Side panels and rear panel in smooth aluminium sheets		
Sky Roof (2 x panoramic skylight 70x50cm crossways) over the seating lounge in the rear	٠	-
Sky roof (second panoramic skylight 75x105cm lengthwise over the seating lounge in the rear) incl. roof lining and lamp	-	
Stable, double-glazed flush-fitting windows with integrated blinds and flyscreens		
Exterior design		
Exterior body painted in white	•	•
Interior design		
Upholstery Samir		
Wood décor Ashton	•	•
Textile equipment		
Carpet, loose	-	•
Carpet, loose	٠	-
Fixed beds with ergonomic wooden slatted frames and 150 mm thick 7-zone premium mattresses made of climate-regulating material		
Furniture layouts		
AirPlus overhead locker rear ventilation to avoid condensation	•	•
Bed convert for seating lounge transverse	•	_
Bed convert for seating lounge transverse	_	
Full body mirror		
Overhead locker doors with soft-close function		
Overhead lockers in the rear area	٠	
U-shaped seating in the lounge with free-standing, rigid table base and surrounding seating and backrest cushions with flexible headrest	—	
U-shaped seating with free-standing, rigid table base and surrounding seating and backrest cushions with flexible headrest		-
Wardrobe floor-to-ceiling with convenient linen drawers in upper area	—	
Kitchen		
Extractor fan (extracted air) with draught stopper	•	•
Fridge (153 I), can be opened on both sides, with integrated oven		_
Fridge (177 I), can be opened on both sides, with integrated oven	_	
Gourmet kitchen: three-ring hob, large drawers with soft-close function, cutting board, apothecary drawers, waste bin and central locking		•
Kitchen overhead locker with illuminated roof lining		
MultiFlex rail system incl. hooks (further accessories via Dethleffs Original Accessories)	٠	
Bathroom		
Equipped with cabinets, storage compartments, hooks, large mirrors and a height-adjustable shower head		
Large bathroom with separate shower and toilet with locking door to the lounge		
	-	
Shower arid		
Shower grid Shower panel and bathroom accessories in black	•	•
	•	
Shower panel and bathroom accessories in black	•	•
Shower panel and bathroom accessories in black Multimedia	•	•
Shower panel and bathroom accessories in black Multimedia Flat-screen TV bracket	•	•

### Standard equipment

A 6820-2	A 7820-2	
_	_	

Heating		
Heating in the seating unit for optimum heat distribution, built-in	•	
Hot-water heating with boiler, automatic drain valve and shut-off valve for the sleeping area and digital control panel	•	
Electrical installation		
Automatic switch-on/disconnect for starter battery, leisure battery and refrigerator	•	
Awning light 12 V	•	٠
Dimmable, indirect ambient lighting on the walls	•	
Electric block with integrated overvoltage protection and separate ground fault circuit breaker	•	٠
Illuminated wardrobe	•	
Indirect ambient lighting above the overhead lockers	•	
Indirect ambient lighting on the walls	•	
Indirect lighting in the bathroom with illuminated shower panel	•	
LED lighting throughout the vehicle	•	
Leisure battery AGM, 95 Ah	•	
Luxus on-board control panel	•	
Number of sockets 1x 12V, 6x 230V, 2x USB	•	-
Number of sockets 1x 12V, 7x 230V, 2x USB	-	
Pre-wiring for solar	•	
Spotlights in the roof lining above the habitation door	•	
Water supply		
Fresh water and waste water tanks installed in double floor (insulated area)	•	
Pressurized water pump system	•	٠
Switch for water pump	•	
Gas supply		
Automatic gas cylinder switchover incl. crash sensor, EisEx and gas filter	•	
Storage space for 2 gas bottles with a filling weight of 11 kg each, with simplified access	•	
Safety		
Smoke detector	•	•

### PACKAGES ALPA COACHBUILT

Package	Dual Battery System Package 2 (7489)	Dual Battery System Package 1 (7488)
Victron PowerAssist and PowerControl	Х	х
Electric block EBL 102	Х	х
Victron control panel above the habitation door	Х	Х
Victron Energy MultiPlus charging/inverter combination 3000W/120A	Х	
336 Ah lithium battery	Х	
Victron Energy MultiPlus charging/inverter combination 1600W/70A		Х
168 Ah lithium battery		Х
Additional weight (kg)*	113	63

#### GT Package ALPA A (13827)

Styling Package (overcab design elements)

Panorama skylight 70 x 50 cm in the overcab

Exterior design GT (rear light moulding with black diffuser, skidplate "red")

High characteristic Dethleffs Exklusiv rear light carrier with ShapeLine LED taillights and 3rd brake light

Additional weight (kg)\*

#### GT Package Silver ALPA A (13828)

Styling Package (overcab design elements)

Panorama skylight 70 x 50 cm in the overcab

Exterior design GT (rear light moulding with black diffuser, skidplate "red")

Side panels in metallic titanium silver

High characteristic Dethleffs Exklusiv rear light carrier with ShapeLine LED taillights and 3rd brake light

Additional weight (kg)\*

 $\triangle$  Not known at the time of publication



The factory installation of optional equipment increases the actual mass of the vehicle and reduces the pay-mass. The additional weight indicated for packages and optional equipment shows the additional weight compared to the standard equipment of the respective model or layout. The total weight of the selected optional equipment must not exceed the manufacturer-specified mass for

optional equipment shown in the model overviews. This is a calculated value for each type and layout that Dethleffs uses to determine the maximum weight available for factory-fitted optional equipment. Detailed information and explanations on the subject of weight can be found in the Legal information section.

23.3

23.3

Optional equipment <sup>*</sup>	Included in package	Additional weight (kg)*	Code	A 6820-2	A 7820-2
Fiat chassis					
Dethleffs 16" alloy wheels (for 3 axles)	_	-9.4	8045	-	0
Weight upgrade					
Weight upgrade to 5,400 kg	_	3.5	7497	-	0
Fiat chassis features					
Hydraulic lifting jacks with automatic levelling and weighing function	_	70	9663	0	0
Tow bar (check permissible gross towing weight for trailer operation)	-	30	273	0	0
Exterior features					
Double floor in rear garage	_	12	1890	0	_
Double floor in rear garage	_	13	1890	_	0
Omnistor cassette awning 5.0 m (electric)	-	40	428	0	—
Omnistor cassette awning 5.0 m (manual)	-	40	697	0	-
Omnistor cassette awning 6.0 m (electric)	—	70	519	—	0
Omnistor cassette awning 6.0 m (manual)	_	64	560	-	0
Opening window in overcab left	-	5	622	0	0
Roof vent with fan	-	1.5	7507	0	0
Storage access in the rear	-	9	1732	0	0
Exterior design					
Side panels in metallic titanium silver	GT	0	511	0	0
Interior design					
Real leather individual <sup>20)</sup>	-	0	9785	0	0
Real leather upholstery Colin	_	0	11952	0	0
Upholstery Melia	—	0	11950	0	0
Bathroom					
Ceramic toilet <sup>21)</sup>	-	9.1	7243	0	—
Macerator toilet with waste-holding tank	-	44	1625	0	0
Toilet ventilation via the roof	—	0.8	1681	0	0
Multimedia					
22" flat-screen TV (incl. DBV-T 2 HD/T, DVB-S2 receiver, DVD, HDMI, wide-angle) <sup>6)</sup>	_	3.2	1799	0	0
32" TV (incl. bracket, DVB-T 2 HD/T, DVB-S2 receiver, HDMI, wide angle) incl. sound board	_	9	9127	0	0
Additional 22" flat-screen TV (incl. DBV-T 2 HD/T, DVB-S2 receiver, DVD, HDMI, wide-angle) <sup>23)</sup>	-	3.5	7490	0	0
Additional flat-screen TV bracket	_	2	1809	0	0
Automatic satellite system 85 Twin	-	16	1637	0	0
Dethleffs Naviceiver incl. DAB+, truck navigation and connection to on-board control panel	-	3.65	9582	0	0
Second reversing camera in rear moulding	-	1	11541	0	0
Top View 360° HD camera <sup>24)</sup>	-	4.5	7173	0	0
Heating					
Electrically heated overcab bed	-	16.5	1740	0	0
Heat exchanger for hot-water heating	-	7.5	565	0	0
Hot-water carpet for the driver's cab	-	3.5	6709	0	0
Air Conditioning					

### \* INFO

The factory installation of optional equipment increases the actual mass of the vehicle and reduces the pay-mass. The additional weight indicated for packages and optional equipment shows the additional weight compared to the standard equipment of the respective model or layout. The total weight of the selected optional equipment must not exceed the manufacturer-specified mass for optional equipment shown in the model overviews. This is a calculated value for each type and layout that Dethleffs uses to determine the maximum weight available for factory-fitted optional equipment. Detailed information and

explanations on the subject of weight can be found in the Legal information section. An increase of load capacity increases the manufacturer-specified mass for optional equipment. The increase results from the higher pay-mass due to the alternative chassis. The increased tare weight of the alternative chassis and, in particular, the weight for any mandatory heavier engine variants (e.g. 180 hp) must be deducted from this. For a more detailed description of all mandatory technical dependencies, please refer to the explanations on the footnotes.

Optional equipment*	Included in package	Additional weight (kg)*	Code	A 6820-2	A 7820-2
Roof A/C	_	38.5	609	0	0
Electrical installation					
Solar power system 100 watt	_	12.6	922	0	0
Water supply					
Outdoor shower (cold water)	_	0.5	793	0	0
Gas supply					
Outdoor gas socket gas pressure 30 mbar	_	1.3	878	0	0
Safety					
2 kg fire extinguisher	_	4	1878	0	0
Alarm system (for door with central locking)	—	0.5	322	0	0
Safe	_	10.5	323	0	0
Packages					
Dual Battery System Package 1	_	63	7488	0	0
Dual Battery System Package 2	—	113	7489	0	0
GT Package ALPA A	-	23.3	13827	0	0
GT Package Silver ALPA A	—	23.3	13828	0	0

O Optional equipment — Not possible 🌒 Standard equipment 🔶 Mandatory 🛆 Not known at the time of publication

GT GT Package



The factory installation of optional equipment increases the actual mass of the vehicle and reduces the pay-mass. The additional weight indicated for packages and optional equipment shows the additional weight compared to the standard equipment of the respective model or layout. The total weight of the selected optional equipment must not exceed the manufacturer-specified mass for optional equipment shown in the model overviews. This is a calculated value for each type and layout that Dethleffs uses to determine the maximum weight available for factory-fitted optional equipment. Detailed information and

explanations on the subject of weight can be found in the Legal information section. An increase of load capacity increases the manufacturer-specified mass for optional equipment. The increase results from the higher pay-mass due to the alternative chassis. The increased tare weight of the alternative chassis and, in particular, the weight for any mandatory heavier engine variants (e.g. 180 hp) must be deducted from this. For a more detailed description of all mandatory technical dependencies, please refer to the explanations on the footnotes.

#### **IMPORTANT INFORMATION REGARDING THE SELECTION OF YOUR MOTORHOME**

The weight specifications and tests for **motorhomes** are uniformly regulated throughout the EU in EU Implementing Regulation No. 2021/535 (until June 2022: EU Implementing Regulation No. 1230/2012). We have summarised and explained the key terms and legal requirements from this **regulation** for you below. Our **dealers** and the Dethleffs configurator on our website offer you additional assistance in configuring your vehicle.

#### 1. Technically permissible maximum laden mass

The technically permissible maximum laden mass of the vehicle (e.g. 3,500 kg) is a mass specification set by the manufacturer which the vehicle must not exceed. Information on the technically permissible maximum laden mass of the model you have chosen can be found in the technical data. If the vehicle exceeds the technically permissible maximum laden mass in everyday driving, this constitutes an administrative offence which may result in a fine.

#### 2. Mass in running order

In simple terms, the **mass in running order** is the basic vehicle with **standard equipment** plus a legally fixed standard weight of 75 kg for the driver. This essentially includes the following items:

- the unladen weight of the vehicle together with the bodywork, including operating fluids such as greases, oils and coolants;
- the **standard equipment**, i.e. all equipment items that are included as standard in the factory-fitted scope of delivery;
- the fresh water tank filled to 100 % in driving mode (driving fill according to manufacturer's specifications;) and an aluminium gas cylinder filled to 100 %;
- the fuel tank, which is 90 % full, including fuel;
- the driver, whose weight regardless of the actual weight is generally specified as 75 kg in accordance with EU law.

Information on the **mass in running order** can be found for each model in our sales documents. It is important to note that the value for **mass in running order** given in the sales documents is a default value determined in the **type-approval procedure** and verified by the authorities. It is legally permissible and possible for the **mass in running order** of the vehicle delivered to you to deviate from the nominal value stated in the sales documents. The legally permissible **tolerance** is ± 5 %. In this way, the EU legislator accounts for the fact that certain fluctuations in the **mass in running order** occur due to variations in the weight of supplied parts as well as due to processes and weather conditions.

These weight deviations can be illustrated by means of an example calculation:

- Mass in running order acc. to sales documents: 2,850 kg
- Legally permissible tolerance of ± 5 %: 142.50 kg
- Legally permissible range of mass in running order: 2,707.50 kg to 2,992.50 kg

The specific range of permissible weight deviations can be found for each model in the technical data. Dethleffs makes great efforts to reduce weight variations to the minimum that is unavoidable for production reasons. **Deviations** at the upper and lower end of the range are therefore very rare; however, they cannot be completely ruled out technically, even with all optimisations. The real weight of the vehicle and compliance with the permissible **tolerance** is therefore checked by Dethleffs by weighing each vehicle at the **end of the line**.

#### 3. Mass of the passengers

The **mass of the passengers** is set a standard value of 75 kg for each seat provided by the manufacturer, regardless of the actual weight of the passengers. The **mass of the driver** is already included in the **mass in running order** (see no. 2 above) and is therefore not included again. In the case of a **motorhome** with four **permitted seats**, the **mass of the passengers** is therefore 3 \* 75 kg = 225 kg.

#### 4. Optional equipment and actual mass of the vehicle

**Optional equipment** (also: additional equipment) includes, according to the legal definition, all optional equipment parts not included in the **standard equipment** which are fitted to the vehicle under the responsibility of the manufacturer – i.e. ex works – and can be ordered by the customer (e.g. awning, bicycle or motorbike carrier, satellite system, solar system, oven, etc.). Information on the individual or package weights of the **optional equipment** that can be ordered can be found in our sales documents. **Optional equipment** in this sense does not include other **accessories** that are retrofitted by the **dealer** or you personally after the vehicle has been delivered ex works.

The **mass of the vehicle in running order** (see no. 2 above) and the mass of the **optional equipment** fitted to a specific vehicle at the factory are together referred to as the **actual mass**. You will find the corresponding information for your vehicle after handover under item 13.2 of the Certificate of Conformity (CoC). Please note that this specification also represents a standardised value. Since the **mass in running order** – as an element of the **actual mass** – is subject to a legally permissible **tolerance** of  $\pm$  5 % (see no. 2), the **actual mass** may also deviate accordingly from the stated nominal value.

#### 5. Pay-mass and minimum pay-mass

The installation of optional equipment is also subject to technical and legal limits: Only so much optional equipment can be ordered and fitted at the factory that sufficient free weight remains for baggage and other accessories ("pay-mass") without exceeding the technically permissible maximum laden mass. The pay-mass is calculated by subtracting the mass in running order (nominal value according to sales documents, see no. 2 above), mass of the optional equipment and the mass of the passengers (see no. 3 above) from the technically permissible maximum laden mass (see no. 1 above). The EU regulations stipulate a fixed minimum pay-mass for motorhomes, which must remain as a minimum for baggage or other non-factory-fitted accessories. This minimum pay-mass is calculated as follows:

Minimum pay-mass in kg  $\geq$  10  $^{*}$  (n + L)

Where: "n" is the maximum number of passengers plus the driver and "L" is the overall length of the vehicle in metres.

For a motorhome with a length of 6 m and 4 approved seats, the minimum pay-mass is therefore e.g. 10 kg \* (4 + 6) = 100 kg. To ensure that the **minimum pay-mass** is maintained, there is a maximum combination of **optional equipment** that can be ordered for each vehicle model. In the above example with a **minimum pay-mass** of 100 kg, the total mass of **optional equipment** for a vehicle with four **permitted seats** and a **mass in running order** of 2,850 kg should not exceed 325 kg:

- 3,500 kg technically permissible maximum laden mass
- 2,850 kg mass in running order
- 3\*75 kg mass of the passengers
- 100 kg minimum pay-mass
- = 325 kg maximum permissible mass of optional equipment

It is important to note that this calculation is based on the default value for mass in running order as defined in the type-approval procedure, without taking into account the permissible weight deviations for mass in running order (see no. 2 above). If the maximum permissible value for the optional equipment of (in the example) 325 kg is almost or completely exhausted, an upward weight deviation can therefore result in the minimum pay-mass of 100 kg being met mathematically using the default value for the mass in running order, although in fact there is no corresponding load capacity. Here, too, an example calculation for a vehicle with four seats, whose real weighed mass in running order is 2 % above the nominal value:

3.500 kg	technically permissible maximum laden mass
- 2.907 kg	real weighed mass in running order (+ 2 % compared to
	the stated value of 2,850 kg)
- 3*75 kg	mass of the passengers
- 325 kg	optional equipment (maximum permissible value)
= 43 kg	actual load capacity (< minimum pay-mass of 100 kg)

In order to avoid such a situation, Dethleffs further reduces the maximum permissible weight of the total **optional equipment** that can be ordered on a model-specific basis. The limitation of **optional equipment** is intended to ensure that the **minimum pay-mass**, i.e. the legally prescribed free mass for **baggage** and retrofitted **accessories**, is actually available for the **vehicle load capacity** of the vehicles delivered by Dethleffs. Since the weight of a specific vehicle can only be determined when it is weighed at the **end of the line**, in very rare cases a situation may arise in which the **minimum pay-mass** at the **end of the line** is not guaranteed, despite this limitation of **optional equipment**. In order to guarantee the **minimum pay-mass** even in these cases, Dethleffs will check together with your **trade partner** and you before delivery of the vehicle whether, for example, the vehicle is loaded up, seats are reduced or **optional equipment** is removed.

### 6. Effects of tolerances of the mass in running order on the pay-mass

Regardless of the minimum pay-mass, you should note that unavoidable production-related fluctuations in the mass in running order – both upwards and downwards – have a mirror-image effect on the remaining load capacity: If you order our example vehicle (see no. 3. above), for example, with optional equipment with a total weight of 150 kg, the calculated pay-mass based on the default value for the mass in running order is 275 kg. The load capacity actually available may deviate from this value due to tolerances and may be higher or lower. If the mass in running order of your vehicle is, for example, permissibly 2 % higher than stated in the sales documents, the load capacity is reduced from 275 kg to 218 kg: 3.500 kg technically permissible maximum laden mass

2.907 kg	real weighed mass in running order (+ 2 % compared to the
	stated value of 2,850 kg)
3*75 kg	mass of the passengers
150 kg	optional equipment ordered for the specific vehicle
= 218 kg	sactual load capacity

As a precaution to ensure that the calculated **pay-mass** is actually given, you should therefore take the possible and permissible **tolerances** for the **mass in running order** into account when configuring your vehicle. We also recommend that you weigh the laden **motorhome** on a non-automatic scale before each journey and, taking the individual weight of the **passengers** into account, determine whether the **technically permissible maximum laden mass** and the **technically permissible maximum mass on the axle** are observed.