Globebus A Class

The most compact A Class motorhome series from Dethleffs drives as easy and dynamic as a van! Ideal for city trips and mountain roads. But despite all its compactness, it knows how to convince with the advantages of a full-grown motorhome such as insulation, freedom of movement and kitchen and bathroom equipment. For those who value striking sporty details, the Gran Turismo equipment package is just right.

Upholstery



+ Upholstery Floyd



+ Upholstery Duke O

Wood décor



+ Wood décor Noce Nagano

O optionally available


Technical info

Overall length, approx.	695 cm
Overall width, approx.	220 cm
Overall height, approx.	281 cm
Headroom in living area, approx.	198 cm

Maximum values partly not possible for all models or only in connection with certain options.

Plus factors

- + Proven Dethleffs quality at an attractive price
- Agile and safe handling due to compact exterior dimensions with an external width of only 2.20 m
- + Sporty, striking Gran Turismo (GT) equipment package (optional)
- + Fully equipped kitchen with 2-burner stove, trash can, multiflex rail system and much more.
- Pleasant sleeping comfort due to 150 mm thick 7-zone cold foam mattresses made of climate-regulating material and ergonomic wooden slatted frames





Globebus A Class Technical info



Globebus A Class		Ι 6
Standard chassis		Fiat Ducato Light Low Platform
Emission standards		Euro 6d Final
Overall length, approx.	cm	695
Overall width, approx.	cm	220
Overall height, approx.	cm	281 ¹⁾
Headroom in living area, approx.	cm	198
Towable load braked/unbraked	kg	2000 / 750
Wheelbase, approx.	mm	3800
Bed dimension: Front bed, L x W, approx.	cm	185 x 150
Bed dimension: Rear bed, L x W, approx.	cm	195 x 80 / 195 x 75 / 200 x 155
Sleeping berths standard / max.		4
Standard engine		140 MultiJet 3
kW (bhp)		103 (140)
Mass in running order (+/-5%)*	kg	2992 (2842 to 3142)*
Manufacturer-specified mass for optional equipment*	kg	173
Technically permissible maximum laden mass*	kg	3499
Permitted number of seats (including driver)*		4
Refrigerator volume (thereof freezer), approx.	T	137 (15)
Waste water tank, approx.		90
Fresh water tank capacity, total/ Fresh water tank capacity at driving filling	I	114 / 20
Measurement storage opening left (W x H)	cm	95 x 85
Measurement storage opening right (W x H)	cm	95 x 105

O Optional equipment — Not possible ● Standard equipment ◆ Mandatory △ Not known at the time of publication

* INFO

The specified mass in running order is a default value defined in the typeapproval procedure. Due to manufacturing tolerances, the actual weighed mass in running order may deviate from the value stated above. Deviations of up to \pm 5 % of the mass in running order are legally permissible and possible. The permissible range in kilograms is given in brackets after the mass in running order. The manufacturer-specified mass for optional equipment is a calculated value for each type and layout that Dethleffs uses to determine the maximum weight available for factory-fitted optional equipment. The limitation of optional equipment is intended to ensure that the minimum pay-mass, i.e. the legally prescribed free mass for baggage and retrofitted accessories, is actually available for the vehicle load capacity of the vehicles delivered by Dethleffs. The real weight of your vehicle ex works can only be determined when it is

weighed at the end of the line. If, in exceptional cases, the weighing shows that the actual load capacity falls below theminimum pay-mass despite limiting the optional equipment due to a permissible weight deviation, we will check together with your trade partner and you whether we should, for example, increase the load capacity of the vehicle, reduce the number of seats or remove optional equipment before delivering the vehicle. The technically permissible maximum laden mass of the vehicle and the technically permissible maximum mass on the axle must not be exceeded. Detailed information & explanations on the subject of weight and the configuration of the vehicle can be found in the section Legal information. For a more detailed description of all mandatory technical dependencies, please refer to the explanations on the footnotes.

Standard equipment

Fiat chassis	
Fiat Ducato Light low platform (3,499 kg), MultiJet 140 (2.2 l / 103 kW / 140 hp), 6-speed manual transmission	-
Right-hand drive chassis	
Steel rims 15" (215/70 R15C) incl. full wheel covers	
Fiat chassis features	
ABS (anti-lock braking system) / EBD (electronic brakeforce distribution)	
Additional protection for radiator through grille at front of vehicle	
Anti-theft device	
Automatic Brake Assist after a collision	
Captain seats: integrated headrests, two armrests, swivel function	
Chassis in right-hand drive version	
Crosswind Assist	
Cruise control	
Cup holder in the centre of the dashboard	
Diesel tank 75 litre incl. 19L AdBlue tank	
Driver and passenger airbags	
Driver and passenger detection	
Driver's cab manual A/C	
ESP incl. ASR, Traction Plus, Hill Holder and Hill Descent Control	
Front-wheel drive	•
Height and tilt adjustable incl. two padded armrests for the driver and front passenger seat	
Low-vibration coach-style exterior mirrors that can be heated and adjusted electrically (two-piece)	•
Pleated blinds in the windscreen and side windows of the drive's cab for the best insulation and privacy	
Rear axle mudflaps	٠
Trailer Stability Assist	
Tyre inflation kit and towing eye	٠
Exterior features	
70 cm wide habitation door	•
70 cm wide habitation door Bedroom window right and left	•
	•
Bedroom window right and left	•
Bedroom window right and left Dethleffs Exclusive rear light carrier with 3rd brake light	• • • •
Bedroom window right and left Dethleffs Exclusive rear light carrier with 3rd brake light Driver's cab door left	• • • •
Bedroom window right and left Dethleffs Exclusive rear light carrier with 3rd brake light Driver's cab door left EPS insulation	• • • •
Bedroom window right and left Dethleffs Exclusive rear light carrier with 3rd brake light Driver's cab door left EPS insulation Floor thickness: 49 mm, side wall thickness: 34mm and roof thickness: 35 mm	• • • • •
Bedroom window right and left Dethleffs Exclusive rear light carrier with 3rd brake light Driver's cab door left EPS insulation Floor thickness: 49 mm, side wall thickness: 34mm and roof thickness: 35 mm Flyscreen habitation door	• • • • • •
Bedroom window right and leftDethleffs Exclusive rear light carrier with 3rd brake lightDriver's cab door leftEPS insulationFloor thickness: 49 mm, side wall thickness: 34mm and roof thickness: 35 mmFlyscreen habitation doorGRP roof	• • • • • • • • • • • • • • • • • • •
Bedroom window right and leftDethleffs Exclusive rear light carrier with 3rd brake lightDriver's cab door leftEPS insulationFloor thickness: 49 mm, side wall thickness: 34mm and roof thickness: 35 mmFlyscreen habitation doorGRP roofHabitation access with comfortable, wide, electric step	
Bedroom window right and left Dethleffs Exclusive rear light carrier with 3rd brake light Driver's cab door left EPS insulation Floor thickness: 49 mm, side wall thickness: 34mm and roof thickness: 35 mm Flyscreen habitation door GRP roof Habitation access with comfortable, wide, electric step Habitation door with window incl. blackout and central locking (incl. cab door) Large rear garage: two garage doors/flaps with turn/tighten lock, rear lowering (150 kg surface load), anti-slip surface, heated, lashing strips, illuminated, 1x	
Bedroom window right and leftDethleffs Exclusive rear light carrier with 3rd brake lightDriver's cab door leftEPS insulationFloor thickness: 49 mm, side wall thickness: 34mm and roof thickness: 35 mmFloor thickness: 49 mm, side wall thickness: 34mm and roof thickness: 35 mmGRP roofHabitation access with comfortable, wide, electric stepHabitation door with window incl. blackout and central locking (incl. cab door)Large rear garage: two garage doors/flaps with turn/tighten lock, rear lowering (150 kg surface load), anti-slip surface, heated, lashing strips, illuminated, 1x 230 V socket	
Bedroom window right and leftDethleffs Exclusive rear light carrier with 3rd brake lightDriver's cab door leftEPS insulationFloor thickness: 49 mm, side wall thickness: 34mm and roof thickness: 35 mmFlyscreen habitation doorGRP roofHabitation access with comfortable, wide, electric stepHabitation door with window incl. blackout and central locking (incl. cab door)Large rear garage: two garage doors/flaps with turn/tighten lock, rear lowering (150 kg surface load), anti-slip surface, heated, lashing strips, illuminated, 1x 230 V socketLifetime construction technology: Tried-and-tested reliable flooring and superstructure with excellent insulation	
Bedroom window right and leftDethleffs Exclusive rear light carrier with 3rd brake lightDriver's cab door leftEPS insulationFloor thickness: 49 mm, side wall thickness: 34mm and roof thickness: 35 mmFloor thickness: 49 mm, side wall thickness: 34mm and roof thickness: 35 mmFlyscreen habitation doorGRP roofHabitation access with comfortable, wide, electric stepHabitation door with window incl. blackout and central locking (incl. cab door)Large rear garage: two garage doors/flaps with turn/tighten lock, rear lowering (150 kg surface load), anti-slip surface, heated, lashing strips, illuminated, 1x 230 V socketLifetime construction technology: Tried-and-tested reliable flooring and superstructure with excellent insulationPanoramic skylight 40x40 cm with flyscreen and blackout blinds above the pull-down bed	
Bedroom window right and leftDethleffs Exclusive rear light carrier with 3rd brake lightDriver's cab door leftEPS insulationFloor thickness: 49 mm, side wall thickness: 34mm and roof thickness: 35 mmFloor thickness: 49 mm, side wall thickness: 34mm and roof thickness: 35 mmFlyscreen habitation doorGRP roofHabitation access with comfortable, wide, electric stepHabitation door with window incl. blackout and central locking (incl. cab door)Large rear garage: two garage doors/flaps with turn/tighten lock, rear lowering (150 kg surface load), anti-slip surface, heated, lashing strips, illuminated, 1x 230 V socketLifetime construction technology: Tried-and-tested reliable flooring and superstructure with excellent insulationPanoramic skylight 40x40 cm with flyscreen and blackout blinds above the pull-down bedPanoramic skylight 75x105 cm above the seating lounge	
Bedroom window right and left Dethleffs Exclusive rear light carrier with 3rd brake light Driver's cab door left EPS insulation Floor thickness: 49 mm, side wall thickness: 34mm and roof thickness: 35 mm Flyscreen habitation door GRP roof Habitation access with comfortable, wide, electric step Habitation door with window incl. blackout and central locking (incl. cab door) Large rear garage: two garage doors/flaps with turn/tighten lock, rear lowering (150 kg surface load), anti-slip surface, heated, lashing strips, illuminated, 1x 230 V socket Lifetime construction technology: Tried-and-tested reliable flooring and superstructure with excellent insulation Panoramic skylight 40x40 cm with flyscreen and blackout blinds above the pull-down bed Panoramic skylight 75x105 cm above the seating lounge Side panels and rear panel made of resistant high-gloss GRP with smooth, shiny surface	
Bedroom window right and leftDethleffs Exclusive rear light carrier with 3rd brake lightDriver's cab door leftEPS insulationFloor thickness: 49 mm, side wall thickness: 34mm and roof thickness: 35 mmFlyscreen habitation doorGRP roofHabitation access with comfortable, wide, electric stepHabitation door with window incl. blackout and central locking (incl. cab door)Large rear garage: two garage doors/flaps with turn/tighten lock, rear lowering (150 kg surface load), anti-slip surface, heated, lashing strips, illuminated, 1x 230 V socketLifetime construction technology: Tried-and-tested reliable flooring and superstructure with excellent insulationPanoramic skylight 40x40 cm with flyscreen and blackout blinds above the pull-down bedPanoramic skylight 75x105 cm above the seating loungeSide panels and rear panel made of resistant high-gloss GRP with smooth, shiny surfaceExterior design	•
Bedroom window right and left Dethleffs Exclusive rear light carrier with 3rd brake light Driver's cab door left FPS insulation Floor thickness: 49 mm, side wall thickness: 34mm and roof thickness: 35 mm Floor thickness: 49 mm, side wall thickness: 34mm and roof thickness: 35 mm Flyscreen habitation door GRP roof Habitation access with comfortable, wide, electric step Habitation door with window incl. blackout and central locking (incl. cab door) Large rear garage: two garage doors/flaps with turn/tighten lock, rear lowering (150 kg surface load), anti-slip surface, heated, lashing strips, illuminated, 1x 230 V socket Lifetime construction technology: Tried-and-tested reliable flooring and superstructure with excellent insulation Panoramic skylight 75x105 cm above the seating lounge Side panels and rear panel made of resistant high-gloss GRP with smooth, shiny surface Exterior design Interior design	•
Bedroom window right and left Dethleffs Exclusive rear light carrier with 3rd brake light Driver's cab door left EPS insulation Floor thickness: 49 mm, side wall thickness: 34mm and roof thickness: 35 mm Floor thickness: 49 mm, side wall thickness: 34mm and roof thickness: 35 mm Flyscreen habitation door GRP roof Habitation access with comfortable, wide, electric step Habitation door with window incl. blackout and central locking (incl. cab door) Large rear garage: two garage doors/flaps with turn/tighten lock, rear lowering (150 kg surface load), anti-slip surface, heated, lashing strips, illuminated, 1x 230 V socket Lifetime construction technology: Tried-and-tested reliable flooring and superstructure with excellent insulation Panoramic skylight 75x105 cm above the seating lounge Side panels and rear panel made of resistant high-gloss GRP with smooth, shiny surface Exterior body painted in white Interior design Upholstery Floyd	•
Bedroom window right and left Dethleffs Exclusive rear light carrier with 3rd brake light Driver's cab door left EPS insulation Floor thickness: 49 mm, side wall thickness: 34mm and roof thickness: 35 mm Flyscreen habitation door GRP roof Habitation access with comfortable, wide, electric step Habitation door with window incl. blackout and central locking (incl. cab door) Large rear garage: two garage doors/flaps with turn/tighten lock, rear lowering (150 kg surface load), anti-slip surface, heated, lashing strips, illuminated, 1x 230 V socket Lifetime construction technology: Tried-and-tested reliable flooring and superstructure with excellent insulation Panoramic skylight 75x105 cm above the seating lounge Side panels and rear panel made of resistant high-gloss GRP with smooth, shiny surface Exterior body painted in white Interior design Upholstery Floyd Wood décor Noce Nagano	•
Bedroom window right and left Dethleffs Exclusive rear light carrier with 3rd brake light Driver's cab door left EFS insulation Floor thickness: 49 mm, side wall thickness: 34mm and roof thickness: 35 mm Flyscreen habitation door GRP roof Habitation access with comfortable, wide, electric step Habitation door with window incl. blackout and central locking (incl. cab door) Large rear garage: two garage doors/flaps with turn/tighten lock, rear lowering (150 kg surface load), anti-slip surface, heated, lashing strips, illuminated, 1x 230 V socket Lifetime construction technology: Tried-and-tested reliable flooring and superstructure with excellent insulation Panoramic skylight 75x105 cm above the seating lounge Side panels and rear panel made of resistant high-gloss GRP with smooth, shiny surface Exterior design Upholstery Floyd Wood décor Noce Nagano Fostile equipment	•
Bedroom window right and left Dethleffs Exclusive rear light carrier with 3rd brake light Driver's cab door left EPS insulation Floor thickness: 49 mm, side wall thickness: 34mm and roof thickness: 35 mm Floor thickness: 49 mm, side wall thickness: 34mm and roof thickness: 35 mm Floor of Habitation door GRP roof Habitation access with comfortable, wide, electric step Habitation door with window incl. blackout and central locking (incl. cab door) Large rear garage: two garage doors/flaps with turn/tighten lock, rear lowering (150 kg surface load), anti-slip surface, heated, lashing strips, illuminated, 1x Z30 V socket Lifetime construction technology: Tried-and-tested reliable flooring and superstructure with excellent insulation Panoramic skylight 75x105 cm above the seating lounge Side panels and rear panel made of resistant high-gloss GRP with smooth, shiny surface Exterior body painted in white Interior design Upholstery Floyd Wood décor Noce Nagano Extelior Noce Nagano Exterior Noce Nagano Exterior Noce Nagano Exterior Noce Nagano Exterior Noce Nagano Florent Exterior Noce Nagano Exterior Noce Nagano	•
Bedroom window right and left Dethleffs Exclusive rear light carrier with 3rd brake light Driver's cab door left EFS insulation Floor thickness: 49 mm, side wall thickness: 34mm and roof thickness: 35 mm Flyscreen habitation door GRP roof Habitation access with comfortable, wide, electric step Habitation door with window incl. blackout and central locking (incl. cab door) Large rear garage: two garage doors/flaps with turn/tighten lock, rear lowering (150 kg surface load), anti-slip surface, heated, lashing strips, illuminated, 1x 230 V socket Lifetime construction technology: Tried-and-tested reliable flooring and superstructure with excellent insulation Panoramic skylight 75x105 cm above the seating lounge Side panels and rear panel made of resistant high-gloss GRP with smooth, shiny surface Exterior design Upholstery Floyd Wood décor Noce Nagano Fostile equipment	•

Standard equipment

Cosy L-shaped lounge with free-standing, rigid table base and two integrated 3-point seatbelts	•
Floor-to-ceiling wooden sliding door to the bedroom	•
Full body mirror	•
High-level single beds incl. comfortable access via steps	•
Manual pull-down bed in the driver's cab	•
Option to convert single beds to double bed	•
Overhead locker doors with soft-close function	•
Wardrobe floor-to-ceiling with convenient linen drawers in upper area	•
Kitchen	
Floor-to-ceiling fridge with separate freezer compartment and automatic energy selection (AES) (137 l)	•
Gourmet kitchen: two-ring hob, large drawers, cutlery tray, bin and generous worktop	•
MultiFlex rail system incl. hooks (further accessories via Dethleffs Original Accessories)	•
Oven in the kitchen floor units	•
Bathroom	
Equipped with cabinets, storage compartments, large mirrors, toothbrush mug and toilet paper holder	
Shower grid	•
Multimedia	
DAB+ radio antenna mounted on the roof Flat-screen TV bracket	•
	•
Pre-wiring for satellite system Preparation for radio system incl. sound package in the driver's cabin	
Heating	
Gas hot-air heating 6kW with 1.8kW electric heating element and hot-water boiler incl. digital control panel	•
Gas hot-air heating 6kW with 1.8kW electric heating element and hot-water boiler incl. digital control panel Electrical installation	•
	•
Electrical installation	•
Electrical installation Automatic switch-on/disconnect for starter battery, leisure battery and refrigerator	•
Electrical installation Automatic switch-on/disconnect for starter battery, leisure battery and refrigerator Awning light 12 V Awning light switched off when ignition on Electric block with integrated overvoltage protection and separate ground fault circuit breaker	•
Electrical installation Automatic switch-on/disconnect for starter battery, leisure battery and refrigerator Awning light 12 V Awning light switched off when ignition on Electric block with integrated overvoltage protection and separate ground fault circuit breaker Indirect ambient lighting above the overhead lockers	•
Electrical installation Automatic switch-on/disconnect for starter battery, leisure battery and refrigerator Awning light 12 V Awning light switched off when ignition on Electric block with integrated overvoltage protection and separate ground fault circuit breaker Indirect ambient lighting above the overhead lockers LED lighting throughout the vehicle	
Electrical installation Automatic switch-on/disconnect for starter battery, leisure battery and refrigerator Awning light 12 V Awning light switched off when ignition on Electric block with integrated overvoltage protection and separate ground fault circuit breaker Indirect ambient lighting above the overhead lockers LED lighting throughout the vehicle Leisure battery AGM, 95 Ah	
Electrical installationAutomatic switch-on/disconnect for starter battery, leisure battery and refrigeratorAwning light 12 VAwning light switched off when ignition onElectric block with integrated overvoltage protection and separate ground fault circuit breakerIndirect ambient lighting above the overhead lockersLED lighting throughout the vehicleLeisure battery AGM, 95 AhLuxus on-board control panel	
Electrical installationAutomatic switch-on/disconnect for starter battery, leisure battery and refrigeratorAwning light 12 VAwning light switched off when ignition onElectric block with integrated overvoltage protection and separate ground fault circuit breakerIndirect ambient lighting above the overhead lockersLED lighting throughout the vehicleLeisure battery AGM, 95 AhLuxus on-board control panelNumber of sockets 1x 12V, 6x 230V, 2x USB	
Electrical installationAutomatic switch-on/disconnect for starter battery, leisure battery and refrigeratorAwning light 12 VAwning light switched off when ignition onElectric block with integrated overvoltage protection and separate ground fault circuit breakerIndirect ambient lighting above the overhead lockersLED lighting throughout the vehicleLeisure battery AGM, 95 AhLuxus on-board control panelNumber of sockets 1x 12V, 6x 230V, 2x USBPre-wiring for solar	
Electrical installationAutomatic switch-on/disconnect for starter battery, leisure battery and refrigeratorAwning light 12 VAwning light switched off when ignition onElectric block with integrated overvoltage protection and separate ground fault circuit breakerIndirect ambient lighting above the overhead lockersLED lighting throughout the vehicleLeisure battery AGM, 95 AhLuxus on-board control panelNumber of sockets 1x 12V, 6x 230V, 2x USB	
Electrical installationAutomatic switch-on/disconnect for starter battery, leisure battery and refrigeratorAwning light 12 VAwning light switched off when ignition onElectric block with integrated overvoltage protection and separate ground fault circuit breakerIndirect ambient lighting above the overhead lockersLED lighting throughout the vehicleLeisure battery AGM, 95 AhLuxus on-board control panelNumber of sockets 1x 12V, 6x 230V, 2x USBPre-wiring for solar	
Electrical installationAutomatic switch-on/disconnect for starter battery, leisure battery and refrigeratorAwning light 12 VAwning light switched off when ignition onElectric block with integrated overvoltage protection and separate ground fault circuit breakerIndirect ambient lighting above the overhead lockersLED lighting throughout the vehicleLeisure battery AGM, 95 AhLuxus on-board control panelNumber of sockets 1x 12V, 6x 230V, 2x USBPre-wiring for solarSpotlights in the roof lining above the habitation door	
Electrical installationAutomatic switch-on/disconnect for starter battery, leisure battery and refrigeratorAwning light 12 VAwning light switched off when ignition onElectric block with integrated overvoltage protection and separate ground fault circuit breakerIndirect ambient lighting above the overhead lockersLED lighting throughout the vehicleLeisure battery AGM, 95 AhLuxus on-board control panelNumber of sockets 1x 12V, 6x 230V, 2x USBPre-wiring for solarSpotlights in the roof lining above the habitation doorWater supply	
Electrical installation Automatic switch-on/disconnect for starter battery, leisure battery and refrigerator Awning light 12 V Awning light switched off when ignition on Electric block with integrated overvoltage protection and separate ground fault circuit breaker Indirect ambient lighting above the overhead lockers LED lighting throughout the vehicle Leisure battery AGM, 95 Ah Luxus on-board control panel Number of sockets 1x 12V, 6x 230V, 2x USB Pre-wiring for solar Spotlights in the roof lining above the habitation door Water supply Fresh water tank in insulated and heated area	
Electrical installation Automatic switch-on/disconnect for starter battery, leisure battery and refrigerator Awning light 12 V Awning light switched off when ignition on Electric block with integrated overvoltage protection and separate ground fault circuit breaker Indirect ambient lighting above the overhead lockers LED lighting throughout the vehicle Leisure battery AGM, 95 Ah Luxus on-board control panel Number of sockets 1x 12V, 6x 230V, 2x USB Pre-wiring for solar Spotlights in the roof lining above the habitation door Water supply Fresh water tank in insulated and heated area Insulated waste water tank	
Electrical installation Automatic switch-on/disconnect for starter battery, leisure battery and refrigerator Awning light 12 V Awning light switched off when ignition on Electric block with integrated overvoltage protection and separate ground fault circuit breaker Indirect ambient lighting above the overhead lockers LED lighting throughout the vehicle Leisure battery AGM, 95 Ah Luxus on-board control panel Number of sockets 1x 12V, 6x 230V, 2x USB Pre-wiring for solar Spotlights in the roof lining above the habitation door Water supply Fresh water tank in insulated and heated area Insulated waste water tank Submersible pump	
Electrical installation Automatic switch-on/disconnect for starter battery, leisure battery and refrigerator Awning light 12 V Awning light switched off when ignition on Electric block with integrated overvoltage protection and separate ground fault circuit breaker Indirect ambient lighting above the overhead lockers LED lighting throughout the vehicle Leisure battery AGM, 95 Ah Luxus on-board control panel Number of sockets 1x 12V, 6x 230V, 2x USB Pre-wiring for solar Spotlights in the roof lining above the habitation door Water supply Fresh water tank in insulated and heated area Insulated waste water tank Submersible pump Gas supply Storage space for 2 gas bottles with a filling weight of 11 kg each	
Electrical installation Automatic switch-on/disconnect for starter battery, leisure battery and refrigerator Awning light 12 V Awning light switched off when ignition on Electric block with integrated overvoltage protection and separate ground fault circuit breaker Indirect ambient lighting above the overhead lockers LED lighting throughout the vehicle Leisure battery AGM, 95 Ah Luxus on-board control panel Number of sockets 1x 12V, 6x 230V, 2x USB Pre-wiring for solar Spotlights in the roof lining above the habitation door Water supply Fresh water tank in insulated and heated area Insulated waste water tank Submersible pump Gas supply	

PACKAGES GLOBEBUS A CLASS

Package	Winter Comfort Package hot-air heating Globebus 16 (8251)
Insulated under-floor pipes	х
Waste water tank and pipes electrically heated	х
Switch for water pump	х
Gas hot-air heating 6kW with 1.8kW electric heating element and hot-water boiler incl. digital control panel	х
Insulated waste water tank	х
XPS insulation	Х
Additional weight (kg)*	28.2

Chassis Package (12125)

Dashboard with aluminium application

Driver's cab automatic A/C Leather steering wheel and gear knob withleather sleeve Electric parking brake Diesel tank 90 litre incl. 19L AdBlue tank Steering wheel with control elements

Additional weight (kg)*

Globebus GT Package (13992)

Electric parking brake Leather steering wheel and gear knob withleather sleeve Dashboard with aluminium application Driver's cab automatic A/C Diesel tank 90 litre incl. 19L AdBlue tank Steering wheel with control elements Alloy wheel Fiat 16 " Exterior design GT (paint of I-front partly black, extended GT stickers, skidplate "red") Kitchen back panel in metallic grey Two-tone sockets and switches Stable, double-glazed flush-fitting windows with integrated blinds and flyscreens High characteristic Dethleffs Exclusive rear light carrier with 3rd brake light

Additional weight (kg)*

 \triangle Not known at the time of publication



The factory installation of optional equipment increases the actual mass of the vehicle and reduces the pay-mass. The additional weight indicated for packages and optional equipment shows the additional weight compared to the standard equipment of the respective model or layout. The total weight of the selected optional equipment must not exceed the manufacturer-specified mass for

optional equipment shown in the model overviews. This is a calculated value for each type and layout that Dethleffs uses to determine the maximum weight available for factory-fitted optional equipment. Detailed information and explanations on the subject of weight can be found in the Legal information section.

4.5

29.5

Optional equipment [*]	Included in package	Additional weight (kg)*	Code	16
Fiat chassis				
Alloy wheel Fiat 16 "	GT	20	8922	0
Fiat Ducato Light low platform (3,499 kg), MultiJet 140 (2.2 l / 103 kW / 140 hp), 9-speed torque converter automatic transmission $^{2)}$	—	35	140A	0
Fiat Ducato Light low platform (3,499 kg), MultiJet 180 (2.2 l / 132 kW / 180 hp), 9-speed torque converter automatic transmission ²⁾	_	35	180A	0
Weight upgrade				
Weight upgrade 3,650 kg	_	0	10769	0
Fiat chassis features				
Rear corner steadies (2 pieces)	-	6	390	0
Reinforced spring for front axle	-	3.75	1889	0
Tow bar (check permissible gross towing weight for trailer operation) ³⁾	_	65	273	0
Exterior features				
Bike rack for 3 bikes (lowerable)	-	20.5	7482	0
Bike rack for 3 bikes (rear)	-	9.6	938	0
Omnistor cassette awning 5.0 m (manual)	-	40	697	0
Panorama skylight 70 x 50 cm above the pull-down bed		6	246	0
Stable, double-glazed flush-fitting windows with integrated blinds and flyscreens	GT	1	415	0
Interior design				
Upholstery Duke	_	0	11949	0
Furniture layouts				
ISOFIX child seat bracket for third and fourth seat facing direction of travel	_	4	8125	0
Bathroom		-		
Additional window in bathroom	_	5	372	0
Multimedia				
Automatic HD satellite system 65 Twin ⁵⁾	-	11	11258	0
Dethleffs Naviceiver incl. DAB+, truck navigation and connection to on-board control panel ⁴⁾	—	3.65	9582	0
Flat screen 22" HD TV (incl. DVD player, HDMI, DVB-S2 satellite receiver and terrestrial DVB-T2 receiver) ^{6) 7)}	-	3.5	11506	0
Rear view camera (single camera)	—	1.1	1642	0
Second reversing camera in rear moulding	_	1	11541	0
Heating				
Floor heating electric (partial) ⁸⁾	_	5	763	0
Air Conditioning				
Roof A/C	_	40	609	0
Electrical installation				
Second leisure battery AGM, 95 Ah ⁹⁾	_	27	830	0
Solar power system 100 watt	-	12.6	922	0
Water supply				
Switch for water pump	WI-KO	0.2	397	0
Gas supply				
Automatic gas cylinder switchover incl. crash sensor, EisEx and gas filter	-	2.5	1577	0

* INFO

The factory installation of optional equipment increases the actual mass of the vehicle and reduces the pay-mass. The additional weight indicated for packages and optional equipment shows the additional weight compared to the standard equipment of the respective model or layout. The total weight of the selected optional equipment must not exceed the manufacturer-specified mass for optional equipment shown in the model overviews. This is a calculated value for each type and layout that Dethleffs uses to determine the maximum weight available for factory-fitted optional equipment. Detailed information and

explanations on the subject of weight can be found in the Legal information section. An increase of load capacity increases the manufacturer-specified mass for optional equipment. The increase results from the higher pay-mass due to the alternative chassis. The increased tare weight of the alternative chassis and, in particular, the weight for any mandatory heavier engine variants (e.g. 180 hp) must be deducted from this. For a more detailed description of all mandatory technical dependencies, please refer to the explanations on the footnotes.

Optional equipment [*]	Included in package	Additional weight (kg)*	Code	16
Outdoor gas socket gas pressure 30 mbar	_	1.3	878	0
Safety				
2 kg fire extinguisher	_	4	1878	0
Alarm system (for door with central locking)	—	0.5	322	0
Safe	_	4.7	323	0
Packages				
Chassis Package	_	4.5	12125	0
Globebus GT Package	—	29.5	13992	0
Winter Comfort Package hot-air heating Globebus I6	—	28.2	8251	0

O Optional equipment — Not possible 🌑 Standard equipment 🔶 Mandatory 🛆 Not known at the time of publication

GT GT Package WI-KO Winter Comfort Package



The factory installation of optional equipment increases the actual mass of the vehicle and reduces the pay-mass. The additional weight indicated for packages and optional equipment shows the additional weight compared to the standard equipment of the respective model or layout. The total weight of the selected optional equipment must not exceed the manufacturer-specified mass for optional equipment shown in the model overviews. This is a calculated value for each type and layout that Dethleffs uses to determine the maximum weight available for factory-fitted optional equipment. Detailed information and

explanations on the subject of weight can be found in the Legal information section. An increase of load capacity increases the manufacturer-specified mass for optional equipment. The increase results from the higher pay-mass due to the alternative chassis. The increased tare weight of the alternative chassis and, in particular, the weight for any mandatory heavier engine variants (e.g. 180 hp) must be deducted from this. For a more detailed description of all mandatory technical dependencies, please refer to the explanations on the footnotes.

IMPORTANT INFORMATION REGARDING THE SELECTION OF YOUR MOTORHOME

The weight specifications and tests for **motorhomes** are uniformly regulated throughout the EU in EU Implementing Regulation No. 2021/535 (until June 2022: EU Implementing Regulation No. 1230/2012). We have summarised and explained the key terms and legal requirements from this **regulation** for you below. Our **dealers** and the Dethleffs configurator on our website offer you additional assistance in configuring your vehicle.

1. Technically permissible maximum laden mass

The technically permissible maximum laden mass of the vehicle (e.g. 3,500 kg) is a mass specification set by the manufacturer which the vehicle must not exceed. Information on the technically permissible maximum laden mass of the model you have chosen can be found in the technical data. If the vehicle exceeds the technically permissible maximum laden mass in everyday driving, this constitutes an administrative offence which may result in a fine.

2. Mass in running order

In simple terms, the **mass in running order** is the basic vehicle with **standard equipment** plus a legally fixed standard weight of 75 kg for the driver. This essentially includes the following items:

- the unladen weight of the vehicle together with the bodywork, including operating fluids such as greases, oils and coolants;
- the **standard equipment**, i.e. all equipment items that are included as standard in the factory-fitted scope of delivery;
- the fresh water tank filled to 100 % in driving mode (driving fill according to manufacturer's specifications;) and an aluminium gas cylinder filled to 100 %;
- the fuel tank, which is 90 % full, including fuel;
- the driver, whose weight regardless of the actual weight is generally specified as 75 kg in accordance with EU law.

Information on the **mass in running order** can be found for each model in our sales documents. It is important to note that the value for **mass in running order** given in the sales documents is a default value determined in the **type-approval procedure** and verified by the authorities. It is legally permissible and possible for the **mass in running order** of the vehicle delivered to you to deviate from the nominal value stated in the sales documents. The legally permissible **tolerance** is ± 5 %. In this way, the EU legislator accounts for the fact that certain fluctuations in the **mass in running order** occur due to variations in the weight of supplied parts as well as due to processes and weather conditions.

These weight deviations can be illustrated by means of an example calculation:

- Mass in running order acc. to sales documents: 2,850 kg
- Legally permissible tolerance of ± 5 %: 142.50 kg
- Legally permissible range of mass in running order: 2,707.50 kg to 2,992.50 kg

The specific range of permissible weight deviations can be found for each model in the technical data. Dethleffs makes great efforts to reduce weight variations to the minimum that is unavoidable for production reasons. **Deviations** at the upper and lower end of the range are therefore very rare; however, they cannot be completely ruled out technically, even with all optimisations. The real weight of the vehicle and compliance with the permissible **tolerance** is therefore checked by Dethleffs by weighing each vehicle at the **end of the line**.

3. Mass of the passengers

The **mass of the passengers** is set a standard value of 75 kg for each seat provided by the manufacturer, regardless of the actual weight of the passengers. The **mass of the driver** is already included in the **mass in running order** (see no. 2 above) and is therefore not included again. In the case of a **motorhome** with four **permitted seats**, the **mass of the passengers** is therefore 3 * 75 kg = 225 kg.

4. Optional equipment and actual mass of the vehicle

Optional equipment (also: additional equipment) includes, according to the legal definition, all optional equipment parts not included in the **standard equipment** which are fitted to the vehicle under the responsibility of the manufacturer – i.e. ex works – and can be ordered by the customer (e.g. awning, bicycle or motorbike carrier, satellite system, solar system, oven, etc.). Information on the individual or package weights of the **optional equipment** that can be ordered can be found in our sales documents. **Optional equipment** in this sense does not include other **accessories** that are retrofitted by the **dealer** or you personally after the vehicle has been delivered ex works.

The **mass of the vehicle in running order** (see no. 2 above) and the mass of the **optional equipment** fitted to a specific vehicle at the factory are together referred to as the **actual mass**. You will find the corresponding information for your vehicle after handover under item 13.2 of the Certificate of Conformity (CoC). Please note that this specification also represents a standardised value. Since the **mass in running order** – as an element of the **actual mass** – is subject to a legally permissible **tolerance** of \pm 5 % (see no. 2), the **actual mass** may also deviate accordingly from the stated nominal value.

5. Pay-mass and minimum pay-mass

The installation of optional equipment is also subject to technical and legal limits: Only so much optional equipment can be ordered and fitted at the factory that sufficient free weight remains for baggage and other accessories ("pay-mass") without exceeding the technically permissible maximum laden mass. The pay-mass is calculated by subtracting the mass in running order (nominal value according to sales documents, see no. 2 above), mass of the optional equipment and the mass of the passengers (see no. 3 above) from the technically permissible maximum laden mass (see no. 1 above). The EU regulations stipulate a fixed minimum pay-mass for motorhomes, which must remain as a minimum for baggage or other non-factory-fitted accessories. This minimum pay-mass is calculated as follows:

Minimum pay-mass in kg \geq 10 * (n + L)

Where: "n" is the maximum number of passengers plus the driver and "L" is the overall length of the vehicle in metres.

For a motorhome with a length of 6 m and 4 approved seats, the minimum pay-mass is therefore e.g. 10 kg * (4 + 6) = 100 kg. To ensure that the **minimum pay-mass** is maintained, there is a maximum combination of **optional equipment** that can be ordered for each vehicle model. In the above example with a **minimum pay-mass** of 100 kg, the total mass of **optional equipment** for a vehicle with four **permitted seats** and a **mass in running order** of 2,850 kg should not exceed 325 kg:

- 3,500 kg technically permissible maximum laden mass
- 2,850 kg mass in running order
- 3*75 kg mass of the passengers
- 100 kg minimum pay-mass
- = 325 kg maximum permissible mass of optional equipment

It is important to note that this calculation is based on the default value for mass in running order as defined in the type-approval procedure, without taking into account the permissible weight deviations for mass in running order (see no. 2 above). If the maximum permissible value for the optional equipment of (in the example) 325 kg is almost or completely exhausted, an upward weight deviation can therefore result in the minimum pay-mass of 100 kg being met mathematically using the default value for the mass in running order, although in fact there is no corresponding load capacity. Here, too, an example calculation for a vehicle with four seats, whose real weighed mass in running order is 2 % above the nominal value:

3.500 kg	technically permissible maximum laden mass
- 2.907 kg	real weighed mass in running order (+ 2 % compared to
	the stated value of 2,850 kg)
- 3*75 kg	mass of the passengers
- 325 kg	optional equipment (maximum permissible value)
= 43 kg	actual load capacity (< minimum pay-mass of 100 kg)

In order to avoid such a situation, Dethleffs further reduces the maximum permissible weight of the total **optional equipment** that can be ordered on a model-specific basis. The limitation of **optional equipment** is intended to ensure that the **minimum pay-mass**, i.e. the legally prescribed free mass for **baggage** and retrofitted **accessories**, is actually available for the **vehicle load capacity** of the vehicles delivered by Dethleffs. Since the weight of a specific vehicle can only be determined when it is weighed at the **end of the line**, in very rare cases a situation may arise in which the **minimum pay-mass** at the **end of the line** is not guaranteed, despite this limitation of **optional equipment**. In order to guarantee the **minimum pay-mass** even in these cases, Dethleffs will check together with your **trade partner** and you before delivery of the vehicle whether, for example, the vehicle is loaded up, seats are reduced or **optional equipment** is removed.

6. Effects of tolerances of the mass in running order on the pay-mass

Regardless of the minimum pay-mass, you should note that unavoidable production-related fluctuations in the mass in running order – both upwards and downwards – have a mirror-image effect on the remaining load capacity: If you order our example vehicle (see no. 3. above), for example, with optional equipment with a total weight of 150 kg, the calculated pay-mass based on the default value for the mass in running order is 275 kg. The load capacity actually available may deviate from this value due to tolerances and may be higher or lower. If the mass in running order of your vehicle is, for example, permissibly 2 % higher than stated in the sales documents, the load capacity is reduced from 275 kg to 218 kg: 3.500 kg technically permissible maximum laden mass

2.907 kg	real weighed mass in running order (+ 2 % compared to the
	stated value of 2,850 kg)
3*75 kg	mass of the passengers
150 kg	optional equipment ordered for the specific vehicle
= 218 kg	sactual load capacity

As a precaution to ensure that the calculated **pay-mass** is actually given, you should therefore take the possible and permissible **tolerances** for the **mass in running order** into account when configuring your vehicle. We also recommend that you weigh the laden **motorhome** on a non-automatic scale before each journey and, taking the individual weight of the **passengers** into account, determine whether the **technically permissible maximum laden mass** and the **technically permissible maximum mass on the axle** are observed.