Globetrotter XL I A Class




This lifestyle luxury motorhome combines spacious living, modern design and genuine driving dynamics. The sporty design language translates a premium wide-track low-platform chassis into real driving experiences. With the Globetrotter XLI, you are just as good on the road as it looks: sporty, dynamic and safe - and thanks to the winterproof double floor construction, 365 days a year.

Technical info	
Overall length, approx.	861 cm
Overall width, approx.	232 cm
Overall height, approx.	304 cm
Headroom in living area, approx.	208 cm

Maximum values partly not possible for all models or only in connection with certain options.

Upholstery







+ Upholstery Melia



+ Real leather upholstery Colin O



+ Real leather individual O

Wood décor



- + Wood décor Amberes Oak
- O optionally available

Plus factors

- + 180 hp (136 kW) Multijet engine, 8-speed torque converter automatic transmission, automatic climate control, multifunction leather steering wheel and much
- + Ideal driving characteristics: Premium low platform chassis with 220 mm lowering and up to 5.4 t gross vehicle mass
- + Absolute winter resistance due to heated raised floor with frost-protected installation.
- + Hot water heating as standard. Comfortable warmth even at the frostiest temperatures. Ideal for allergy sufferers, as no dust whirling up.
- + Lifetime Plus superstructure technology with absolutely rot-proof and durable wall construction
- + Gourmet kitchen with mineral countertop, 3-burner high-efficiency stove, generous drawers with soft-close retraction and central locking, apothecary pull-out, and more
- + Spacious bathroom with sliding door to the bedroom





































Globetrotter XL I A Class		I 7850-2 DBM	I 7850-2 EB
Standard chassis		Fiat Ducato Maxi AL-KO Low Platform 3-axle	Fiat Ducato Maxi AL-KO Low Platform 3-axle
Emission standards		Euro VI-E	Euro VI-E
Overall length, approx.	cm	861	861
Overall width, approx.	cm	232	232
Overall height, approx.	cm	304 1)	304 1)
Headroom in living area, approx.	cm	208	208
Towable load braked/unbraked	kg	1800 / 750	1800 / 750
Wheelbase, approx.	mm	4500	4500
Bed dimension: Front bed, L x W, approx.	cm	200 x 150	200 x 150
Bed dimension: Central / middle bed, L X W, approx.	cm	206 x 150 - 90 O	206 x 150 - 95 O
Bed dimension: Rear bed, L x W, approx.	cm	200 x 150	210 x 200 - 145 / 2x 200 x 82
Sleeping berths standard / max.		4/50	4/50
Standard engine		180 MultiJet 3 Power	180 MultiJet 3 Power
kW (bhp)		132 (180)	132 (180)
Mass in running order (+/-5%)*	kg	4131 (3924 to 4338)*	4129 (3923 to 4335)*
Manufacturer-specified mass for optional equipment*	kg	508	510
Technically permissible maximum laden mass*	kg	5000	5000
Permitted number of seats (including driver)*		4 - 5 🔿	4 - 5 🔾
Refrigerator volume (thereof freezer), approx.	1	177 (35)	177 (35)
Waste water tank, approx.	1	156	156
Fresh water tank capacity, total/ Fresh water tank capacity at driving filling	I	166 / 20	166 / 20
Measurement storage opening left (W x H)	cm	100 x 105	100 x 80 O / 100 x 110
Measurement storage opening right (W x H)	cm	100 x 105	100 x 80 O / 100 x 110

O Optional equipment ─ Not possible ● Standard equipment ◆ Mandatory △ Not known at the time of publication



The specified mass in running order is a default value defined in the type-approval procedure. Due to manufacturing tolerances, the actual weighed mass in running order may deviate from the value stated above. Deviations of up to $\pm\,5$ % of the mass in running order are legally permissible and possible. The permissible range in kilograms is given in brackets after the mass in running order. The manufacturer-specified mass for optional equipment is a calculated value for each type and layout that Dethleffs uses to determine the maximum weight available for factory-fitted optional equipment. The limitation of optional equipment is intended to ensure that the minimum pay-mass, i.e. the legally prescribed free mass for baggage and retrofitted accessories, is actually available for the vehicle load capacity of the vehicles delivered by Dethleffs. The real weight of your vehicle ex works can only be determined when it is

weighed at the end of the line. If, in exceptional cases, the weighing shows that the actual load capacity falls below theminimum pay-mass despite limiting the optional equipment due to a permissible weight deviation, we will check together with your trade partner and you whether we should, for example, increase the load capacity of the vehicle, reduce the number of seats or remove optional equipment before delivering the vehicle. The technically permissible maximum laden mass of the vehicle and the technically permissible maximum mass on the axle must not be exceeded. Detailed information & explanations on the subject of weight and the configuration of the vehicle can be found in the section Legal information. For a more detailed description of all mandatory technical dependencies, please refer to the explanations on the footnotes.

Standard equipment

17850-2 DBM 17850-2 EB

Fiat chassis		
Alloy wheel FIAT 16", black (for 3-axle)		
Fiat Ducato Maxi ALKO low platform 3-axle (5,000 kg) MultiJet 180 (2.2 l / 132 kW / 180 hp) Heavy Duty, 8-speed torque converter automatic transmission		
Right-hand drive chassis		
Fiat chassis features		
ABS (anti-lock braking system) / EBD (electronic brakeforce distribution)		
Additional protection for radiator through grille at front of vehicle		
Automatic Brake Assist after a collision		
Automatic cab air conditioning, digital speedometer with 7" instrument cluster and wireless phone charger in the centre console		
Captain seat with integrated headrest, rotatable, height and tilt adjustable incl. two padded armrests		
Chassis in right-hand drive version		
Crosswind Assist		
Cruise control		
Cup holder in the centre of the dashboard		
Dashboard with aluminium application		
Diesel tank 90 litre incl. 19L AdBlue tank		
Driver and passenger airbags		
Driver and passenger detection		
ESP incl. ASR, Traction Plus, Hill Holder and Hill Descent Control		
Electric windscreen blinds		
Front-wheel drive		
Leather steering wheel and gear knob withleather sleeve		
Low-vibration coach-style exterior mirrors that can be heated and adjusted electrically (two-piece)		
Rear corner steadies (2 pieces)		
Reinforced spring for front axle Right-hand drive with exhaust on the left side		
Steering wheel with control elements Trailor Stability Assist		
Trailer Stability Assist Type inflation bit and touring aver-		
Tyre inflation kit and towing eye Wister turns M. Compine (with specuficular)		
Winter tyres M+S Camping (with snowflake)		
Exterior features		
70 cm wide habitation door with window and blind	•	•
Bedroom window right and left		
Central locking for the drive's cab, habitation and garage door	•	•
Dethleffs Exclusive GRP rear in modern coach look with ShapeLine LED taillights and integrated 3rd brake light		
Double floor storage, some of which can be loaded across almost the entire vehicle width	•	•
Double-glazed flush-fitting windows with blackout & mosquito protection		
Driver's cab door left	•	•
Electric closing aid for habitation door		
Floor thickness: 43 mm, side wall thickness: 34mm and roof thickness: 35 mm	•	•
Flyscreen habitation door		
GRP roof		•
Habitation access with comfortable coupe entrance		
Habitation access with comfortable, wide, electric step	•	•
Lifetime Plus construction technology: rot-free superstructure with no wood inserts, XPS insulation with GRP cladding on the underslung and roof	•	•
Panoramic skylight 40x40 cm with flyscreen and blackout blinds above the pull-down bed	•	•
Panoramic skylight 75x105 cm above the seating lounge	•	
Rear garage: two garage door with one-hand operation, rear lowering (250 kg), heated, lashing rails, LED lights across the entire width, 230 V socket, GRP anti-slip flooring and fleece cove	•	•
Side panels and rear panel in smooth aluminium sheets	•	•
Exterior design		
Exterior body painted in white		
Extensi body pointed in writte		

Standard equipment

1 /850-2 DBM 1 7850-2 FB

	178	178
Interior design		
Upholstery Samir		
Wood décor Amberes Oak		
Textile equipment		
Carpet, loose		_
Carpet, loose		
Rear beds with ergonomic wooden slatted frames and 150 mm thick 7-zone premium mattresses made of climate-regulating material		
Furniture layouts		
AirPlus overhead locker rear ventilation to avoid condensation		_
Cosy L-shaped lounge with free-standing, rigid table base and two integrated 3-point seatbelts		
Double bed high		
Electric pull-down bed in the driver's cab		
Floor-to-ceiling wooden sliding door to the bedroom	•	
Full body mirror		
High-level single beds incl. comfortable access via steps	_	•
No steps in living room		
Option to convert single beds to double bed	_	•
Overhead locker doors with soft-close function		
Sideboard incl. pull-out leg support, drawers and illuminated wall panels	•	•
Wardrobe floor-to-ceiling with convenient linen drawers in upper area		
Wardrobe to the left and right of the queen-size bed	•	
Kitchen		
Extractor fan (extracted air) with draught stopper	•	•
Fridge (177 I), can be opened on both sides, with integrated oven		
Gourmet kitchen: three-ring hob, large drawers with soft-close function, cutting board, apothecary drawers, waste bin and central locking	•	•
Worktop made of solid surface material		
Bathroom		
Equipped with cabinets, storage compartments, hooks, large mirrors and a height-adjustable shower head	•	•
Large bathroom with separate shower and toilet with locking door to the lounge	•	•
Shower grate		
Shower panel and bathroom accessories in black	•	•
Window in bathroom		
Multimedia		
DAB+ radio antenna mounted on the roof	•	•
Flat-screen TV bracket	•	•
Integrated single-lens rear view camera		
Pre-wiring for satellite system	•	
Preparation for additional flat screen		
Preparation for radio system incl. sound package in the driver's cabin	•	•
Second rear view camera in rear moulding	•	•
Heating		
Heat exchanger for hot-water heating	•	•
Hot-water heating with boiler, automatic drain valve and shut-off valve for the sleeping area and digital control panel		
Air Conditioning		
Pre-wiring for roof A/C	•	-
Electrical installation		
Automatic switch-on/disconnect for starter battery, leisure battery and refrigerator		
Awning light 12 V		
Dethleffs connect - System Control Unit		
Electric block with integrated overvoltage protection and separate ground fault circuit breaker	•	•
LED lighting throughout the vehicle		
	•	_

I 7850-2 DBM Standard equipment Leisure battery AGM, 95 Ah Light Moments: Continuous canopy with indirect lighting Light Moments: Indirect ambient lighting above the overhead lockers Light Moments: Indirect dimmable wall surface ambient lighting Light Moments: Indirect lighting in the bathroom with illuminated shower panel Light Moments: Indirect lighting of the sideboard/side couch on the right and of the entrance module as well as of the kitchen tall cupboard Light Moments: illuminated kitchen splashback Light Moments: plinth lighting throughout the vehicle Number of sockets 1x 12V, 8x 230V, 2x USB Pre-wiring for solar Premium on-board control panel with touchscreen Spotlights in the roof lining above the habitation door Two-tone sockets and switches Water supply Fresh water and waste water tanks installed in double floor (insulated area) Pressurized water pump system Switch for water pump **Gas supply** Automatic gas cylinder switchover incl. crash sensor, EisEx and gas filter Storage space for 2 gas bottles with a filling weight of 11 kg each, with simplified access Safety

Smoke detector

PACKAGES GLOBETROTTER XL I A CLASS

Package	Dual Battery System Package 1 (7488)	Dual Battery System Package 2 (7489)
Victron PowerAssist and PowerControl	Х	Х
Electric block EBL 102	Χ	X
Victron control panel above the habitation door	Х	Х
Victron Energy MultiPlus charging/inverter combination 1600W/70A	Х	
168 Ah lithium battery	Х	
Victron Energy MultiPlus charging/inverter combination 3000W/120A		Х
336 Ah lithium battery		Х
Additional weight (kg)*	63	113

GT Package (14589)

LED low beam

Lateral sun shades, as a roller blind for driver and passenger

Panorama skylight 70 x 50 cm in the bedroom

Interior design GT incl. extended kitchen back panel

Additional weight (kg)* 10.4

△ Not known at the time of publication



The factory installation of optional equipment increases the actual mass of the vehicle and reduces the pay-mass. The additional weight indicated for packages and optional equipment shows the additional weight compared to the standard equipment of the respective model or layout. The total weight of the selected optional equipment must not exceed the manufacturer-specified mass for

optional equipment shown in the model overviews. This is a calculated value for each type and layout that Dethleffs uses to determine the maximum weight available for factory-fitted optional equipment. Detailed information and explanations on the subject of weight can be found in the Legal information section.

Optional equipment*	Included in package	Additional weight (kg)*	Code	I 7850-2 DBM	I 7850-2 EB
Weight upgrade					
Weight upgrade to 5,400 kg		0.5	7497	0	0
Fiat chassis features					
Extra seat incl. side couch instead of sideboard ^{21) 22) 8)}	_	11	435	0	0
Hydraulic lifting jacks with automatic levelling and weighing function	_	70	9663	0	0
LED low beam	_	0.5	7152	0	0
SKA captain seat with air suspension	_	20	7505	0	0
Seat heating and ventilation of the seat area ^{14) 15)}	-	0	11147	0	0
Tow bar (check permissible gross towing weight for trailer operation)	-	30	273	0	0
Exterior features					
Double floor in rear garage	_	5	1890	0	0
Omnistor cassette awning 6.0 m (electric)	_	70	519	0	0
Omnistor cassette awning 6.0 m (manual)	_	64	560	0	0
Panorama skylight 70 x 50 cm in the bedroom	_	6	246	0	0
Roof vent with fan	_	1.5	7507	0	0
Exterior design					
Exterior paint on the front bonnet, GRP rear and side panels in metallic titanium silver	_	2.5	511	0	0
Interior design					
Real leather individual ^{14) 16)}	_	0	9785	0	0
Real leather upholstery Colin ¹⁴⁾	_	0	11952	0	0
Upholstery Melia	_	0	11950	0	0
Furniture layouts					
Bed convert for seating lounge transverse ²³⁾	_	9	1944	0	
ISOFIX child seat bracket for third and fourth seat facing direction of travel		4	8125	0	0
Low single-beds for comfortable access and high headroom	_	20.5	510		0
Overhead lockers in the driver's cab instead of pull-down bed	_	-40	679	0	0
Kitchen	-		0.7		
	_	0.3	202		
Winter cover for refrigerator vents		0.3	282		
Bathroom					
Ceramic toilet ¹⁷⁾	_	9.1	7243	0	0
Macerator toilet with waste-holding tank	_	48	1625	0	0
Toilet ventilation via the roof ¹⁷⁾		0.8	1681	0	0
Multimedia					
32" Smart TV incl. flat screen holder	_	8	9807	0	0
Additional 22' flat screen incl. flat screen bracket	_	5.5	7490+1809	0	0
Automatic satellite system 85 Twin	_	16	1637	0	0
Dethleffs Naviceiver incl. DAB+, truck navigation, wireless Apple CarPlay and Android Auto 5)	_	3.65	9582	0	0
Sound Package Plus 5)	_	15.5	8082	0	0
Top View 360° HD camera ^{18) 19)}		4.5	7173	0	0
Heating					
Hot-water carpet for the driver's cab	_	3.5	6709	0	0



The factory installation of optional equipment increases the actual mass of the vehicle and reduces the pay-mass. The additional weight indicated for packages and optional equipment shows the additional weight compared to the standard equipment of the respective model or layout. The total weight of the selected optional equipment must not exceed the manufacturer-specified mass for actional equipment change in the model programs. This is a calculated to the contract of the selected optional equipment change in the model programs. This is a calculated to the contract of the selected optional equipment in the model programs. optional equipment shown in the model overviews. This is a calculated value for each type and layout that Dethleffs uses to determine the maximum weight available for factory-fitted optional equipment. Detailed information and

explanations on the subject of weight can be found in the Legal information section. An increase of load capacity increases the manufacturer-specified mass for optional equipment. The increase results from the higher pay-mass due to the alternative chassis. The increased tare weight of the alternative chassis and, in particular, the weight for any mandatory heavier engine variants (e.g. 180 hp) must be deducted from this. For a more detailed description of all mandatory technical dependencies, please refer to the explanations on the footnotes. footnotes.

Optional equipment*	Included in package	Additional weight (kg)*	Code	I 7850-2 DBM	I 7850-2 EB
Air Conditioning					
Roof A/C	_	38.5	609	0	0
Electrical installation					
Solar power system 100 watt	_	12.6	922	0	0
Water supply					
Outdoor shower installed in rear garage (hot/cold water)	_	2.4	1574	0	0
Gas supply					
Outdoor gas socket gas pressure 30 mbar	_	1.3	878	0	0
Safety					
2 kg fire extinguisher	_	4	1878	0	0
Alarm system (for door with central locking)	_	0.5	322	0	0
Safe	_	4.7	323	0	0
Packages					
Dual Battery System Package 1 ⁶⁾	_	63	7488	0	0
Dual Battery System Package 2 ⁶⁾	_	113	7489	0	0
GT Package	_	10.4	14589	0	0

O Optional equipment — Not possible Standard equipment lack Mandatory Δ Not known at the time of publication



The factory installation of optional equipment increases the actual mass of the vehicle and reduces the pay-mass. The additional weight indicated for packages and optional equipment shows the additional weight compared to the standard equipment of the respective model or layout. The total weight of the selected optional equipment must not exceed the manufacturer-specified mass for optional equipment shown in the model overviews. This is a calculated value for each type and layout that Dethleffs uses to determine the maximum weight available for factory-fitted optional equipment. Detailed information and

explanations on the subject of weight can be found in the Legal information section. An increase of load capacity increases the manufacturer-specified mass for optional equipment. The increase results from the higher pay-mass due to the alternative chassis. The increased tare weight of the alternative chassis and, in particular, the weight for any mandatory heavier engine variants (e.g. 180 hp) must be deducted from this. For a more detailed description of all mandatory technical dependencies, please refer to the explanations on the footnotes. footnotes.

IMPORTANT INFORMATION REGARDING THE SELECTION OF YOUR MOTORHOME

The weight specifications and tests for **motorhomes** are uniformly regulated throughout the EU in EU Implementing Regulation No. 2021/535 (until June 2022: EU Implementing Regulation No. 1230/2012). We have summarised and explained the key terms and legal requirements from this **regulation** for you below. Our **dealers** and the Dethleffs configurator on our website offer you additional assistance in configuring your vehicle.

1. Technically permissible maximum laden mass

The technically permissible maximum laden mass of the vehicle (e.g. 3,500 kg) is a mass specification set by the manufacturer which the vehicle must not exceed. Information on the technically permissible maximum laden mass of the model you have chosen can be found in the technical data. If the vehicle exceeds the technically permissible maximum laden mass in everyday driving, this constitutes an administrative offence which may result in a fine.

2. Mass in running order

In simple terms, the mass in running order is the basic vehicle with standard equipment plus a legally fixed standard weight of 75 kg for the driver. This essentially includes the following items:

- the unladen weight of the vehicle together with the bodywork, including operating fluids such as greases, oils and coolants;
- the standard equipment, i.e. all equipment items that are included as standard in the factory-fitted scope of delivery;
- the fresh water tank filled to 100 % in driving mode (driving fill according to manufacturer's specifications;) and an aluminium gas cylinder filled to
- the fuel tank, which is 90 % full, including fuel;
- the driver, whose weight regardless of the actual weight is generally specified as 75 kg in accordance with EU law.

Information on the **mass in running order** can be found for each model in our sales documents. It is important to note that the value for **mass in running order** given in the sales documents is a default value determined in the **type-approval procedure** and verified by the authorities. It is legally permissible and possible for the **mass in running order** of the vehicle delivered to you to deviate from the nominal value stated in the sales documents. The legally permissible **tolerance** is ± 5 %. In this way, the EU legislator accounts for the fact that certain fluctuations in the **mass in running order** occur due to variations in the weight of supplied parts as well as due to processes and weather conditions.

These weight deviations can be illustrated by means of an example calculation:

- Mass in running order acc. to sales documents: 2,850 kg
- Legally permissible tolerance of ± 5 %: 142.50 kg
- Legally permissible range of **mass in running order**: 2,707.50 kg to 2,992.50 kg

The specific range of permissible weight deviations can be found for each model in the technical data. Dethleffs makes great efforts to reduce weight variations to the minimum that is unavoidable for production reasons. **Deviations** at the upper and lower end of the range are therefore very rare; however, they cannot be completely ruled out technically, even

with all optimisations. The real weight of the vehicle and compliance with the permissible **tolerance** is therefore checked by Dethleffs by weighing each vehicle at the **end of the line**.

3. Mass of the passengers

The **mass of the passengers** is set a standard value of 75 kg for each seat provided by the manufacturer, regardless of the actual weight of the passengers. The **mass of the driver** is already included in the **mass in running order** (see no. 2 above) and is therefore not included again. In the case of a **motorhome** with four **permitted seats**, the **mass of the passengers** is therefore 3 * 75 kg = 225 kg.

4. Optional equipment and actual mass of the vehicle

Optional equipment (also: additional equipment) includes, according to the legal definition, all optional equipment parts not included in the **standard equipment** which are fitted to the vehicle under the responsibility of the manufacturer – i.e. ex works – and can be ordered by the customer (e.g. awning, bicycle or motorbike carrier, satellite system, solar system, oven, etc.). Information on the individual or package weights of the **optional equipment** that can be ordered can be found in our sales documents. **Optional equipment** in this sense does not include other accessories that are retrofitted by the **dealer** or you personally after the vehicle has been delivered ex works.

The mass of the vehicle in running order (see no. 2 above) and the mass of the optional equipment fitted to a specific vehicle at the factory are together referred to as the actual mass. You will find the corresponding information for your vehicle after handover under item 13.2 of the Certificate of Conformity (CoC). Please note that this specification also represents a standardised value. Since the mass in running order – as an element of the actual mass – is subject to a legally permissible tolerance of ± 5 % (see no. 2), the actual mass may also deviate accordingly from the stated nominal value.

5. Pay-mass and minimum pay-mass

The installation of optional equipment is also subject to technical and legal limits: Only so much optional equipment can be ordered and fitted at the factory that sufficient free weight remains for baggage and other accessories ("pay-mass") without exceeding the technically permissible maximum laden mass. The pay-mass is calculated by subtracting the mass in running order (nominal value according to sales documents, see no. 2 above), mass of the optional equipment and the mass of the passengers (see no. 3 above) from the technically permissible maximum laden mass (see no. 1 above). The EU regulations stipulate a fixed minimum pay-mass for motorhomes, which must remain as a minimum for baggage or other non-factory-fitted accessories. This minimum pay-mass is calculated as follows:

Minimum pay-mass in kg \geq 10 * (n + L)

Where: "n" is the maximum number of passengers plus the driver and "L" is the overall length of the vehicle in metres.

For a motorhome with a length of 6 m and 4 approved seats, the minimum pay-mass is therefore e.g. 10 kg * (4 + 6) = 100 kg.

To ensure that the minimum pay-mass is maintained, there is a maximum combination of optional equipment that can be ordered for each vehicle model. In the above example with a minimum pay-mass of 100 kg, the total mass of optional equipment for a vehicle with four permitted seats and a mass in running order of 2,850 kg should not exceed 325 kg:

3,500 kg technically permissible maximum laden mass

- 2,850 kg mass in running order
 - 3*75 kg mass of the passengers
 - 100 kg minimum pay-mass

325 kg maximum permissible mass of optional equipment

It is important to note that this calculation is based on the default value for mass in running order as defined in the type-approval procedure, without taking into account the permissible weight deviations for mass in running order (see no. 2 above). If the maximum permissible value for the optional equipment of (in the example) 325 kg is almost or completely exhausted, an upward weight deviation can therefore result in the minimum pay-mass of 100 kg being met mathematically using the default value for the mass in running order, although in fact there is no corresponding load capacity. Here, too, an example calculation for a vehicle with four seats, whose real weighed mass in running order is 2 % above the nominal value:

3.500 kg technically permissible maximum laden mass
- 2.907 kg real weighed mass in running order (+ 2 % compared to the stated value of 2,850 kg)
- 3*75 kg mass of the passengers

- 325 kg optional equipment (maximum permissible value) = 43 kg actual load capacity (< minimum pay-mass of 100 kg)

In order to avoid such a situation, Dethleffs further reduces the maximum permissible weight of the total **optional equipment** that can be ordered on a model-specific basis. The limitation of **optional equipment** is intended to ensure that the **minimum pay-mass**, i.e. the legally prescribed free mass for **baggage** and retrofitted **accessories**, is actually available for the **vehicle load capacity** of the vehicles delivered by Dethleffs. Since the weight of a specific vehicle can only be determined when it is weighed at the **end of the line**, in very rare cases a situation may arise in which the **minimum pay-mass** at the **end of the line** is not guaranteed, despite this limitation of **optional equipment**. In order to guarantee the **minimum pay-mass** even in these cases, Dethleffs will check together with your **trade partner** and you before delivery of the vehicle whether, for example, the vehicle is loaded up, seats are reduced or **optional equipment** is removed.

6. Effects of tolerances of the mass in running order on the pay-mass

Regardless of the minimum pay-mass, you should note that unavoidable production-related fluctuations in the mass in running order – both upwards and downwards – have a mirror-image effect on the remaining load capacity: If you order our example vehicle (see no. 3. above), for example, with optional equipment with a total weight of 150 kg, the calculated pay-mass based on the default value for the mass in running order is 275 kg. The load capacity actually available may deviate from this value due to tolerances and may be higher or lower. If the mass in running or-

der of your vehicle is, for example, permissibly 2 % higher than stated in the sales documents, the **load capacity** is reduced from 275 kg to 218 kg:

3.500 kg technically permissible maximum laden mass

2.907 kg $\,$ real weighed mass in running order (+ 2 % compared to the

stated value of 2,850 kg) 3*75 kg mass of the passengers

150 kg **optional equipment** ordered for the specific vehicle

= 218 kg sactual load capacity

As a precaution to ensure that the calculated pay-mass is actually given, you should therefore take the possible and permissible tolerances for the mass in running order into account when configuring your vehicle. We also recommend that you weigh the laden motorhome on a non-automatic scale before each journey and, taking the individual weight of the passengers into account, determine whether the technically permissible maximum laden mass and the technically permissible maximum mass on the axle are observed.